



16-Port 10/100Mbps PoE Switch TPE-S160[V1.0R]

The 16-Port 10/100Mbps PoE Switch, model TPE-S160, reduces equipment and installation costs by delivering data and power over existing Ethernet cables to Power over Ethernet (PoE) enabled devices such as Access Points and IP Cameras. Boost office efficiency and reduce network congestion with a total switching capacity of 3.2Gbps.

LED indicators display device status for easy power management and troubleshooting. An internal power supply reduces clutter and delivers 15.4 Watts to each PoE port. A convenient on/off button is located on the back of the switch. Non-PoE devices can connect to the switch—auto-sensing PoE technology cuts power to non-PoE connected devices. Use TRENDnet's PoE Splitter to install non-PoE devices in remote locations.

FEATURES

- 16 x 10/100/1000Mbps Auto-MDIX RJ-45 PoE ports
- On/off power switch
- IEEE 802.3af Power over Ethernet (PoE) compliant
- Supports PoE Powered Device (PD) classification
- Provides 15.4 watts per PoE port
- 3.2Gbps switching fabric
- Full wire-speed non-blocking reception and transmission
- Store-and-forward switching method
- Back pressure Flow Control for half-duplex mode
- IEEE 802.3x Flow Control for full-duplex mode
- 1.5Mbits RAM Data Buffer
- 4K MAC address entries
- Diagnostic LEDs (Power, Link/Activity, PoE Act/Status)
- Plug and Play
- Sturdy 19" wide metal enclosure
- Rack mounting hardware included
- 3-year limited warranty

16-Port 10/100Mbps PoE Switch

TPE-S160(V1.0R)



SPECIFICATIONS

HARDWARE


| | |
|---------------------------|---|
| Standards | • IEEE 802.3 10Base-T • IEEE 802.3u 100Base-TX • IEEE 802.3af Power over Ethernet • IEEE 802.3x Flow Control; |
| Ports | • 16 x 10/100Mbps Auto-MDIX PoE ports |
| Data Transfer Rate | • Ethernet: 10/20Mbps (half/full duplex) • Fast Ethernet: 100/200Mbps (half/full duplex) |
| Data RAM Buffer | • 1.5 Mbps |
| Address Table | • 4K MAC entries |
| Power Switch | • On / off power button |
| Switch Fabric | • 3.2Gbps |
| Power | • 100~240VAC 50/60Hz, internal universal switching power |
| Diagnostic LEDs | • Power, Link/Activity, PoE Act/Status |
| Power Consumption | • 6 Watts max. (no Powered Device (PD) connected) • 260 Watts max. (16 PoE devices connected) |
| Temperature | • Operating: 0° ~ 45°C (32° ~ 113°F) • Storage: -10° ~ 70°C (14° ~ 158°F) |
| Humidity | • Max. 95% (non-condensing) |
| Dimensions | • 440 x 220 x 44 mm (17.3 x 8.7 x 1.7 in.) |
| Weight | • 3.1 kg (6.9 lbs.) |
| Certifications | • CE, FCC |

PoE

| | |
|----------------------------|--|
| Power over Ethernet | • Up to 15.4 watts per port; PD classification • Polymer switch for short protection • PoE: pin 3,6 for power+ and pin 1,2 for power- |
|----------------------------|--|

NETWORKING SOLUTIONS

16-Port 10/100Mbps PoE Switch (TPE-S160)



PACKAGE CONTENTS

| |
|---|
| TPE-S160 |
| Multi-Language Quick Installation Guide |
| Rackmount hardware |
| Power cord (1.8 m / 6 ft.) |

RELATED PRODUCTS

| | |
|------------------|--|
| TV-IP512P | ProView PoE Internet Camera |
| TPE-112GS | Gigabit Power over Ethernet (PoE) Splitter |
| TPE-80WS | 8-Port Gigabit Web Smart PoE Switch |

CONTACT INFORMATION

TRENDnet®

20675 Manhattan Place, Torrance, CA 90501 USA
Tel: 1-310-961-5500
Fax: 1-310-961-5511
Web: www.trendnet.com
Email: sales@trendnet.com
1-888-326-6061

