

APC Back-UPS® 500

Part number: BC500-RS



Battery Backup with Schuko Sockets for Electronics and Computers

The Back-UPS 500 by APC protects your electronic equipment from damage due to power outages, surges and spikes while providing short term battery power during an outage. The Back-UPS 500 protects your equipment and network connection in harsh power environments, ensuring maximum productivity and maintaining work efficiency.

Product Applications:

- PC and peripherals
- Networking equipment (router, modem)
- Network Attached Storage (NAS)
- Game console
- Projector with impulse power
- Landline cordless phone



Product Features:

- 3 Schuko “Battery Backup & Surge Protected” Sockets**
Utilize battery backup and surge protected outlets to protect critical electronic equipment that require battery back-up along with surge protection, so you can save your work and protect your data when the power goes out or fluctuates at dangerous levels.
- 2 Year Warranty**
APC offers a 2 year warranty with free technical phone and online support, APC offers a 2 year warranty with free technical phone and online support, assuring customer peace of mind
- 1 Schuko “Surge Only” Socket**
“Surge Only” outlets protect your secondary electronics (printers, fax machines, etc.) from harmful surges and spikes without reducing battery capacity used to run primary electronics during power outages.
- Push Button Circuit Breaker**
Provides for easy recovery from circuit overloads and protects your fuse box and electronics from electrical damage.
- LED Indicator and Audible Alarms**
Quickly understand the unit and power status through visual and audible indicators.



Specifications

Model Number	BC500-RS
Output	
Output Capacity	500 VA / 300 Watts
Output Voltage / Frequency (On utility)	230V / 50/60+/-3Hz
Output Voltage / Frequency (On battery)	230V +/-8%, 50 or 60 Hz +/-1 Hz (auto-sensing)
Output Connections	4 Schuko sockets (3 with battery backup and surge protection and 1 with surge protection only)
Waveform Type	Stepped Approximation to Sine Wave
Input	
Maximum adjustable Input Voltage / Frequency	160 – 278 V / 50/60Hz +/-3Hz (default: 180-266V, 50Hz)
Input Connection	1.2M power cable with Schuko plug
Surge Protection	
AC Power Surge Protection	All sockets
Physical	
Unit Dimensions (H x W x D)	200 x 115 x 256 mm
Unit Weight	5.5 Kg
Shipping Dimensions (H x W x D)	343.5 x 200 x 278.5 mm
Shipping Weight	6.2 Kg
Color	Black
UPC Code	731304305569
Battery	
Battery Type	Maintenance-free, sealed lead-acid battery, leak proof
Battery Size	12 volt, 7.2 Ah
Management	
Alarms	Visual (LED) and audible alarms
Adjustable Sensitivity and Transfer Voltage	Low, Medium (default), High

APC by Schneider Electric

132 Fairgrounds Rd
West Kingston, RI 02892

www.apc.com

