



Digitech Pro 650VA

TECNICAL SPECS	
GENERAL PROPERTIES	
Product Code	
TSK1574	
EAN Code	
8697842802019	
Series description	
Digitech Pro	
Product description	
Digitech Pro 650 VA	
Capacity / Power	
650 VA / 360 W	
Display	
LCD Panel	
Alarm	
Battery mode, Low battery, Over load, Error	
INPUT	
Low voltage transfer	
162 VAC	
Low voltage correction	
- %10	
High voltage transfer	
290 VAC	
High voltage correction	
+%10	
Frequency range	
50 / 60 Hz $\pm$ %5	
Phase	
1 Phase + Neutral + Ground	
OUTPUT	
Output voltage	
220 VAC / 2 pcs Earth Outlet	
Frequency range sync. mode	
50 / 60 Hz $\pm$ %4	
Frequency range battery mode	
50 $\pm$ 0.25 Hz - 60 $\pm$ 0.3 Hz	
Transfer time Line to battery	
4 ms	

Wave type

Simulated sine wave

BATTERY PROPERTIES**Battery type**

12V / 9 Ah

Battery quantity

1

Charging time

up to %90 capacity 6 Hour

Charge voltage

14.0 VDC

Charge current

1.0 A

COMMUNICATION and SOFTWARE**Supported interface**

USB

Supported OS Software

Windows / Linux / Mac OS

DIMENSIONS and WEIGHTH**Product dimention (DxHxW) (mm)**

317x158x125

Product weigth with battery

4.15 Kg

Product weigth without battery

-

Package dimention (DxHxW) (mm)

373x228x155

Package weigth with battery

5.15 Kg

Package weigth without battery

-

Master carton dimention (DxHxW)

385x260x495

Master carton weigth with battery

15.40 Kg

Master carton weigth without batt.

-

Product quantity in master carton

3 Adet

ENVIRONMENTAL FACTOR**Operation temperature range (°C)**

0°C - 40°C

Humidity (%)

%20 - %90 non-condensing

Noise (dBA)

<40 dB