



HP 1810 Switch Series



Key features

- Customized operation using intuitive Web interface
- Flexible connection and deployment options
- Layer 2 operation at wire speeds
- Fanless design for quiet operation
- Lifetime warranty

Energy Efficient Ethernet (EEE) and idle-port power down. HP 1810 switches have a lifetime warranty.

Product overview

HP 1810 Switch Series devices are smart-managed, fixed-configuration Gigabit Ethernet and Fast Ethernet Layer 2 switches designed for small businesses looking for key features in an easy-to-administer solution.

The series includes 8- and 24-port Gigabit Ethernet and Fast Ethernet models and a 48-port Gigabit Ethernet switch. Some models include SFP ports for fiber connectivity and some are fanless, making them ideal for office deployments. All 1810 Switches support flexible installation options, including mounting on walls, under tables, or on desktops. The 8-port Gigabit Ethernet model can be powered by an upstream Power over Ethernet (PoE) switch for environments where no line power is available.

Customizable features include VLANs, Spanning Tree, and link aggregation trunking; 8- and 24-port switches offer Rapid Spanning Tree Protocol (RSTP) and DSCP QoS policies. The 8- and 24-port models also include the latest energy-saving capabilities, including

Features and benefits

Connectivity

- **Auto-MDI/MDIX**
automatically adjusts for straight-through or crossover cables on all ports
- **Packet storm protection**
protects against broadcast, multicast, or unicast storms with user-defined thresholds
- **IEEE 802.3af PoE-powered device option**
obtains power provided by a standard PoE device connected to Port 1; deploy the switch wherever an Ethernet cable can reach as a power outlet is not needed (8-port GbE model only)
- **SFP ports for fiber connectivity**
provides fiber connections for uplinks and other connections across longer distances than copper cabling can support; "true" SFP ports operate in addition to available copper Ethernet ports, providing a higher total number of available ports vs. "combo" ports, which are either a copper or fiber connection

Performance

- **Half-/full-duplex auto-negotiating capability on every port**
doubles the throughput of every port
- **Link aggregation (trunking)**
brings together groups of ports automatically using Link Aggregation Control Protocol (LACP) or, manually, to form an ultra-high-bandwidth connection to the network backbone; helps prevent traffic bottlenecks; the 8-port models have four trunks of four links each, the 24-port models have eight trunks of four links each, and the 1810-48G switch has 16 trunks of eight links each

Quality of Service (QoS)

- **Traffic prioritization (IEEE 802.1p)**
allows real-time traffic classification with eight priority levels mapped to four queues
- **IEEE 802.1p prioritization with DSCP**
delivers data from the switch to devices based on the priority and type of traffic using Differentiated Services Code Point (DSCP); available only with v2 switch models
- **Broadcast control**
allows limitation of broadcast traffic rate to cut down on unwanted network broadcast traffic

Layer 2 switching

- **VLAN support and tagging**
supports up to 64 port-based VLANs and dynamic configuration of IEEE 802.1Q VLAN tagging, providing security between workgroups
- **Jumbo packet support**
improves the performance of large data transfers; supports frame size of up to 9220 bytes

Resiliency and high availability

- **IEEE 802.1D Spanning Tree Protocol (STP) and IEEE 802.1W Rapid Spanning Tree Protocol (RSTP)**
provides redundant links while preventing network loops; available only with v2 switch models

Security

- **Secure Sockets Layer (SSL)**
encrypts all HTTP traffic, allowing secure access to the browser-based management GUI in the switch
- **Automatic denial-of-service protection**
monitors six types of malicious attacks and protects the network by blocking the attacks
- **Management password**
provides security so that only authorized access to the Web browser interface is allowed

Ease of use

- **Locator LED (switch)**
allows users to set the locator LED on a specific switch to either turn on, blink, or turn off; simplifies troubleshooting by making it easy to locate a particular switch within a rack of similar switches
- **Comprehensive LED display with per-port indicators**
provides an at-a-glance view of status, activity, speed, and full-duplex operation

Flexibility

- **Flexible installation**
allows mounting on wall, desktop, or under-table
- **Rack mountable (24- and 48-port models)**
offers a rack-mounting option with included hardware
- **Kensington lock slot**
allows switches to be physically secured in open-space deployments

Management

- **Simple Web management**
allows easy management of devices by nontechnical users with its intuitive Web GUI
- **Secure Web GUI**
provides a secure, easy-to-use graphical interface for configuring the module via HTTPS
- **SNMPv1, v2c**
enables devices to be discovered and monitored from an SNMP management station
- **Dual flash images**
provides independent primary and secondary operating system files for backup while upgrading
- **Port mirroring**
enables traffic on a port to be simultaneously sent to a network analyzer for monitoring

- **IEEE 802.1AB Link Layer Discovery Protocol (LLDP)**
advertises and receives management information from adjacent devices on a network, facilitating easy mapping by network management applications

Additional information

- **Energy savings**
utilizes Energy Efficient Ethernet (EEE) IEEE 802.3az standard for lower power consumption; available only with v2 switch models
- **Green IT and power**
places inactive ports automatically in low-power mode, and its LED in power-down mode, to conserve energy
- **Green initiative support**
provides support for RoHS and WEEE regulations

Warranty and support

- **Lifetime warranty**
for as long as you own the product with advance replacement and next-business-day delivery (available in most countries)†
- **Electronic and telephone support**
limited electronic and telephone support is available from HP; to reach our support centers, refer to **www.hp.com/networking/contact-support**; for details on the duration of support provided with your product purchase, refer to **www.hp.com/networking/warrantysummary**

†HP warranty includes repair or replacement of hardware for as long as you own the product, with next business day advance replacement (available in most countries). The disk drive included with HP AllianceOne Advanced Services and Services z1 Modules, HP Threat Management Services z1 Module, HP AllianceOne Extended z1 Module with Riverbed Steelhead, HP MSM765z1 Mobility Controller and HP Survivable Branch Communication z1 Module powered by Microsoft Lync has a five-year hardware warranty. For details, refer to the Software license and hardware warranty statements at **www.hp.com/networking/warranty**.

HP 1810 Switch Series

Specifications



HP 1810-8G v2 Switch (J9802A)



HP 1810-24G v2 Switch (J9803A)



HP 1810-48G Switch (J9660A)

Ports	8 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only Supports a maximum of 8 autosensing 10/100/1000 ports	24 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only 2 SFP 100/1000 Mbps ports Supports a maximum of 24 autosensing 10/100/1000 ports plus 2 SFP ports	48 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only 4 SFP 100/1000 Mbps ports Supports a maximum of 48 autosensing 10/100/1000 ports plus 4 SFP ports
Physical characteristics	7.93(w) x 4.65(d) x 1.73(h) in (20.14 x 11.81 x 4.39 cm) (1U height) Weight 0.84 lb (.38 kg)	12.99(w) x 6.81(d) x 1.73(h) in (32.99 x 17.3 x 4.39 cm) (1U height) Weight 2.54 lb (1.15 kg)	17.4(w) x 9.75(d) x 1.75(h) in (44.2 x 24.77 x 4.45 cm) (1U height) Weight 6.31 lb (2.86 kg)
Memory and processor	128 MB RAM, 8 MB flash; packet buffer size: 512 KB	128 MB RAM, 8 MB flash; packet buffer size: 512 KB	64 MB RAM, 8 MB flash; packet buffer size: 1.5 MB
Mounting	wall, desktop, and under-table mounting	Mounts in an EIA-standard 19 in. telco rack (hardware included); horizontal surface, wall, and under-table mounting	Mounts in an EIA-standard 19 in. telco rack (hardware included); wall, desktop, tabletop, and under-table mounting
Performance	100 Mb Latency < 3.3 μs (64-byte packets) 1000 Mb Latency < 2.3 μs (64-byte packets) Throughput up to 11.9 million pps Switching capacity 16 Gb/s MAC address table size 8000 entries	< 3.3 μs (64-byte packets) < 2.2 μs (64-byte packets) up to 38.7 million pps 52 Gb/s 8000 entries	< 8.4 μs (64-byte packets) < 3.2 μs (64-byte packets) up to 77.4 million pps (64-byte packets) 104 Gb/s 16000 entries
Environment	Operating temperature 32°F to 104°F (0°C to 40°C) Operating relative humidity 15% to 95% @ 104°F (40°C) Nonoperating/Storage temperature -40°F to 158°F (-40°C to 70°C) Nonoperating/Storage relative humidity 15% to 95% @ 140°F (60°C) Altitude up to 10,000 ft (3 km) Acoustic Power: 0 dB no fan	32°F to 104°F (0°C to 40°C) 15% to 95% @ 104°F (40°C) -40°F to 158°F (-40°C to 70°C) 15% to 95% @ 140°F (60°C) up to 10,000 ft (3 km) Power: 0 dB no fan	32°F to 113°F (0°C to 45°C) 15% to 95% @ 104°F (40°C), noncondensing -40°F to 158°F (-40°C to 70°C) 15% to 90% @ 149°F (65°C), noncondensing up to 10,000 ft (3 km) Power: 22 dB single fan
Electrical characteristics	Frequency 50/60 Hz Maximum heat dissipation Voltage 100-240 VAC Current .5 A Maximum power rating 7.2 W Notes Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.	50/60 Hz 100-127/200-240 VAC .4/.3 A 22 W Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.	50/60 Hz 204 BTU/hr (215.22 kJ/hr) 100-127/200-240 VAC 0.9/0.5 A 60 W Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety	UL 60950-1; IEC 60950; EN 60950	UL 60950-1; IEC 60950; EN 60950	CSA 22.2 No. 60950; EN 60950/IEC 60950; UL 60950
Emissions	EN 55022 Class A; CISPR 22 Class A; VCCI V-3; FCC (CFR 47, Part 15) Subpart B Class A; VCCI V-4	EN 55022 Class A; CISPR 22 Class A; VCCI V-3; FCC (CFR 47, Part 15) Subpart B Class A; VCCI V-4	EN 55022 Class A; CISPR 22 Class A; VCCI V-3; FCC (CFR 47, Part 15) Subpart B Class A; VCCI V-4
Immunity	ESD IEC 61000-4-2 Radiated IEC 61000-4-3 EFT/Burst IEC 61000-4-4 Surge IEC 61000-4-5 Conducted IEC 61000-4-6 Power frequency magnetic field IEC 61000-4-8 Voltage dips and interruptions IEC 61000-4-11 Harmonics EN 61000-3-2 Flicker EN 61000-3-3	IEC 61000-4-2 IEC 61000-4-3 IEC 61000-4-4 IEC 61000-4-5 IEC 61000-4-6 IEC 61000-4-8 IEC 61000-4-11 EN 61000-3-2 EN 61000-3-3	IEC 61000-4-2 IEC 61000-4-3 IEC 61000-4-4 IEC 61000-4-5 IEC 61000-4-6 IEC 61000-4-8 IEC 61000-4-11 EN 61000-3-2 EN 61000-3-3
Management	Web browser	Web browser	Web browser

HP 1810 Switch Series

Specifications (continued)

	HP 1810-8G v2 Switch (J9802A)	HP 1810-24G v2 Switch (J9803A)	HP 1810-48G Switch (J9660A)
Notes	Use only supported genuine HP mini-GBICs with your switch.	Use only supported genuine HP mini-GBICs with your switch.	Use only supported genuine HP mini-GBICs with your switch.
Services	<p>3-year, 4-hour onsite, 13x5 coverage for hardware (UE256E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (UE257E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UE258E)</p> <p>3-year, 24x7 SW phone support, software updates (UE260E)</p> <p>Installation with minimum configuration, system-based pricing (U4826E)</p> <p>Installation with HP-provided configuration, system-based pricing (U4830E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UR846E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UR847E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UR848E)</p> <p>4-year, 24x7 SW phone support, software updates (UR849E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (UR850E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware (UR851E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UR852E)</p> <p>5-year, 24x7 SW phone support, software updates (UR853E)</p> <p>3 Yr 6 hr Call-to-Repair Onsite (UW383E)</p> <p>4 Yr 6 hr Call-to-Repair Onsite (UW384E)</p> <p>5 Yr 6 hr Call-to-Repair Onsite (UW385E)</p> <p>1-year, 4-hour onsite, 13x5 coverage for hardware (HR899E)</p> <p>1-year, 4-hour onsite, 24x7 coverage for hardware (HR900E)</p> <p>1-year, 6 hour Call-To-Repair Onsite for hardware (HR903E)</p> <p>1-year, 24x7 software phone support, software updates (HR902E)</p> <p>1-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support and software updates (HR901E)</p> <p>1-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HU347E)</p> <p>1-year, 24x7 software phone support, software updates + 4 hour hardware exchange (HU348E)</p> <p>3-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HU349E)</p> <p>3-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HU350E)</p> <p>4-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS810E)</p>	<p>3-year, 4-hour onsite, 13x5 coverage for hardware (U4683E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (U4835E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (U6321E)</p> <p>3-year, 24x7 SW phone support, software updates (UF792E)</p> <p>Installation with minimum configuration, system-based pricing (U4826E)</p> <p>Installation with HP-provided configuration, system-based pricing (U4830E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UR948E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UR949E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UR950E)</p> <p>4-year, 24x7 SW phone support, software updates (UR951E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (UR952E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware (UR953E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UR954E)</p> <p>5-year, 24x7 SW phone support, software updates (UR955E)</p> <p>3 Yr 6 hr Call-to-Repair Onsite (UW368E)</p> <p>4 Yr 6 hr Call-to-Repair Onsite (UW369E)</p> <p>5 Yr 6 hr Call-to-Repair Onsite (UW370E)</p> <p>1-year, 4-hour onsite, 13x5 coverage for hardware (HR849E)</p> <p>1-year, 4-hour onsite, 24x7 coverage for hardware (HR850E)</p> <p>1-year, 6 hour Call-To-Repair Onsite for hardware (HR853E)</p> <p>1-year, 24x7 software phone support, software updates (HR852E)</p> <p>1-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support and software updates (HR851E)</p> <p>1-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS554E)</p> <p>1-year, 24x7 software phone support, software updates + 4 hour hardware exchange (HS555E)</p> <p>3-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS556E)</p> <p>3-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS557E)</p> <p>4-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS558E)</p>	<p>3-year, 4-hour onsite, 13x5 coverage for hardware (HS854E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (HS856E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (U6321E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (HS858E)</p> <p>3-year, 24x7 SW phone support, software updates (UF792E)</p> <p>3-year, 24x7 SW phone support, software updates (HS859E)</p> <p>1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HS846E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HS848E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HS850E)</p> <p>Installation with minimum configuration, system-based pricing (U4826E)</p> <p>Installation with HP-provided configuration, system-based pricing (U4830E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (HS862E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (HS864E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (HS866E)</p> <p>4-year, 24x7 SW phone support, software updates (HS867E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (HS870E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware (HS872E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (HS874E)</p> <p>5-year, 24x7 SW phone support, software updates (HS875E)</p> <p>3 Yr 6 hr Call-to-Repair Onsite (HS860E)</p> <p>3 Yr 6 hr Call-to-Repair Onsite (UW368E)</p> <p>4 Yr 6 hr Call-to-Repair Onsite (HS868E)</p> <p>5 Yr 6 hr Call-to-Repair Onsite (HS876E)</p> <p>1-year, 6 hour Call-To-Repair Onsite for hardware (HS852E)</p> <p>1-year, 24x7 software phone support, software updates (HS851E)</p> <p>Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>

HP 1810 Switch Series

Specifications (continued)

HP 1810-8G v2 Switch (J9802A)	HP 1810-24G v2 Switch (J9803A)	HP 1810-48G Switch (J9660A)
<p>4-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS811E)</p> <p>5-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS812E)</p> <p>5-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS813E)</p> <p>Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>	<p>4-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS559E)</p> <p>5-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS560E)</p> <p>5-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS561E)</p> <p>Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>	

HP 1810 Switch Series

Specifications (continued)



HP 1810-8 v2 Switch (J9800A)



HP 1810-24 v2 Switch (J9801A)

Ports	<p>7 RJ-45 autosensing 10/100 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full</p> <p>1 RJ-45 autosensing 10/100/1000 port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only</p> <p>Supports a maximum of 7 autosensing 10/100 ports plus 1 autosensing 10/100/1000 ports</p>	<p>22 RJ-45 autosensing 10/100 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full</p> <p>2 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only</p> <p>2 SFP 100/1000 Mbps ports</p> <p>Supports a maximum of 22 autosensing 10/100 ports plus 2 autosensing 10/100/1000 ports plus 2 SFP ports</p>
Physical characteristics	<p>7.93(w) x 4.65(d) x 1.73(h) in (20.14 x 11.81 x 4.39 cm) (1U height)</p> <p>Weight 0.77 lb (.35 kg)</p>	<p>12.99(w) x 6.81(d) x 1.73(h) in (32.99 x 17.3 x 4.39 cm) (1U height)</p> <p>2.2 lb (1 kg)</p>
Memory and processor	128 MB RAM, 8 MB flash; packet buffer size: 512 KB	128 MB RAM, 8 MB flash; packet buffer size: 512 KB
Mounting	wall, desktop, and under-table mounting	Mounts in an EIA-standard 19 in. telco rack (hardware included); horizontal surface, wall, and under-table mounting
Performance		
100 Mb Latency	< 3.3 μs (64-byte packets)	< 3.4 μs (64-byte packets)
Throughput	up to 2.5 million pps	up to 9.2 million pps
Switching capacity	3.4 Gb/s	12.4 Gb/s
MAC address table size	8000 entries	8000 entries
Environment		
Operating temperature	32°F to 104°F (0°C to 40°C)	32°F to 104°F (0°C to 40°C)
Operating relative humidity	15% to 95% @ 104°F (40°C)	15% to 95% @ 104°F (40°C)
Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)	-40°F to 158°F (-40°C to 70°C)
Nonoperating/Storage relative humidity	15% to 95% @ 140°F (60°C)	15% to 95% @ 140°F (60°C)
Altitude	up to 10,000 ft (3 km)	up to 10,000 ft (3 km)
Acoustic	Power: 0 dB no fan	Power: 0 dB no fan
Electrical characteristics		
Frequency	50/60 Hz	50/60 Hz
Voltage	100-240 VAC	100-127/200-240 VAC
Current	.5 A	.4/.3 A
Maximum power rating	4.8 W	22 W
Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety	UL 60950-1; IEC 60950; EN 60950	UL 60950-1; IEC 60950; EN 60950
Emissions	EN 55022 Class A; CISPR 22 Class A; VCCI V-3; FCC (CFR 47, Part 15) Subpart B Class A; VCCI V-4	EN 55022 Class A; CISPR 22 Class A; VCCI V-3; FCC (CFR 47, Part 15) Subpart B Class A; VCCI V-4
Immunity		
ESD	IEC 61000-4-2	IEC 61000-4-2
Radiated	IEC 61000-4-3	IEC 61000-4-3
EFT/Burst	IEC 61000-4-4	IEC 61000-4-4
Surge	IEC 61000-4-5	IEC 61000-4-5
Conducted	IEC 61000-4-6	IEC 61000-4-6
Power frequency magnetic field	IEC 61000-4-8	IEC 61000-4-8
Voltage dips and interruptions	IEC 61000-4-11	IEC 61000-4-11
Harmonics	EN 61000-3-2	EN 61000-3-2
Flicker	EN 61000-3-3	EN 61000-3-3
Management	Web browser	Web browser
Notes	Use only supported genuine HP mini-GBICs with your switch.	Use only supported genuine HP mini-GBICs with your switch.
Services	<p>3-year, 4-hour onsite, 13x5 coverage for hardware (UE256E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (UE257E)</p>	<p>3-year, 4-hour onsite, 13x5 coverage for hardware (U4683E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (U4835E)</p>

HP 1810 Switch Series

Specifications (continued)

HP 1810-8 v2 Switch (J9800A)	HP 1810-24 v2 Switch (J9801A)
3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UE258E)	3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (U6321E)
3-year, 24x7 SW phone support, software updates (UE260E)	3-year, 24x7 SW phone support, software updates (UF792E)
Installation with minimum configuration, system-based pricing (U4826E)	Installation with minimum configuration, system-based pricing (U4826E)
Installation with HP-provided configuration, system-based pricing (U4830E)	Installation with HP-provided configuration, system-based pricing (U4830E)
4-year, 4-hour onsite, 13x5 coverage for hardware (UR846E)	4-year, 4-hour onsite, 13x5 coverage for hardware (UR948E)
4-year, 4-hour onsite, 24x7 coverage for hardware (UR847E)	4-year, 4-hour onsite, 24x7 coverage for hardware (UR949E)
4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UR848E)	4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UR950E)
4-year, 24x7 SW phone support, software updates (UR849E)	4-year, 24x7 SW phone support, software updates (UR951E)
5-year, 4-hour onsite, 13x5 coverage for hardware (UR850E)	5-year, 4-hour onsite, 13x5 coverage for hardware (UR952E)
5-year, 4-hour onsite, 24x7 coverage for hardware (UR851E)	5-year, 4-hour onsite, 24x7 coverage for hardware (UR953E)
5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UR852E)	5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UR954E)
5-year, 24x7 SW phone support, software updates (UR853E)	5-year, 24x7 SW phone support, software updates (UR955E)
3 Yr 6 hr Call-to-Repair Onsite (UW383E)	3 Yr 6 hr Call-to-Repair Onsite (UW368E)
4 Yr 6 hr Call-to-Repair Onsite (UW384E)	4 Yr 6 hr Call-to-Repair Onsite (UW369E)
5 Yr 6 hr Call-to-Repair Onsite (UW385E)	5 Yr 6 hr Call-to-Repair Onsite (UW370E)
1-year, 4-hour onsite, 13x5 coverage for hardware (HR899E)	1-year, 4-hour onsite, 13x5 coverage for hardware (HR849E)
1-year, 4-hour onsite, 24x7 coverage for hardware (HR900E)	1-year, 4-hour onsite, 24x7 coverage for hardware (HR850E)
1-year, 6 hour Call-To-Repair Onsite for hardware (HR903E)	1-year, 6 hour Call-To-Repair Onsite for hardware (HR853E)
1-year, 24x7 software phone support, software updates (HR902E)	1-year, 24x7 software phone support, software updates (HR852E)
1-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support and software updates (HR901E)	1-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support and software updates (HR851E)
1-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HU347E)	1-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS54E)
1-year, 24x7 software phone support, software updates + 4 hour hardware exchange (HU348E)	1-year, 24x7 software phone support, software updates + 4 hour hardware exchange (HS55E)
3-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HU349E)	3-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS56E)
3-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HU350E)	3-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS57E)
4-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS810E)	4-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS58E)
4-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS811E)	4-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS59E)
5-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS812E)	5-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS60E)
5-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS813E)	5-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS61E)
Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Standards and Protocols

(applies to all products in series)

Denial of service protection

CPU DoS Protection

General protocols

IEEE 802.1p Priority

IEEE 802.1Q VLANs

IEEE 802.3x Flow Control

IEEE 802.3ad Link Aggregation Control Protocol (LACP)

RFC 1534 DHCP/BOOTP Interoperation

Network management

IEEE 802.1AB Link Layer Discovery Protocol (LLDP)

HP 1810 Switch Series accessories

Cables

HP 0.5 m Multimode OM3 LC/LC Optical Cable (AJ833A)
HP 1 m Multimode OM3 LC/LC Optical Cable (AJ834A)
HP 2 m Multimode OM3 LC/LC Optical Cable (AJ835A)
HP 5 m Multimode OM3 LC/LC Optical Cable (AJ836A)
HP 15 m Multimode OM3 LC/LC Optical Cable (AJ837A)
HP 30 m Multimode OM3 LC/LC Optical Cable (AJ838A)
HP 50 m Multimode OM3 LC/LC Optical Cable (AJ839A)
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 1m Cable (QK732A)
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 2m Cable (QK733A)
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 5m Cable (QK734A)
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 15m Cable (QK735A)
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 30m Cable (QK736A)
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 50m Cable (QK737A)

Mounting Kit

HP X410 1U Universal 4-post Rack Mounting Kit (J9583A)

HP 1810-24G v2 Switch (J9803A)

HP X111 100M SFP LC FX Transceiver (J9054C)
HP X121 1G SFP LC SX Transceiver (J4858C)
HP X121 1G SFP LC LX Transceiver (J4859C)
HP X121 1G SFP RJ45 T Transceiver (J8177C)

HP 1810-48G Switch (J9660A)

HP X121 1G SFP LC SX Transceiver (J4858C)
HP X121 1G SFP LC LX Transceiver (J4859C)
HP X121 1G SFP RJ45 T Transceiver (J8177C)

HP 1810-24 v2 Switch (J9801A)

HP X111 100M SFP LC FX Transceiver (J9054C)
HP X121 1G SFP LC SX Transceiver (J4858C)
HP X121 1G SFP LC LX Transceiver (J4859C)
HP X121 1G SFP RJ45 T Transceiver (J8177C)

To learn more, visit hp.com/networking

© Copyright 2009-2013 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Microsoft is a U.S. registered trademark of Microsoft Corporation.

4AA2-6799ENW, Created June 2009; Updated July 2013, Rev. 8

